








# Shanghai Xinfan Industrial Corporation






## Cable Security Seals

Model No.	Product Image	Cable Diameter (mm)	Cable Length	Lock Head Size (mm)	Materials of Locking Head	Tensil (kgf)	Type of Length / Locking	Classification Rating	Characteristics
TSS-K		1.8	220mm or customized	12*27mm hexagonal shape	galvanized low-carbon steel and ABS plastic covered	150	Fixed Length	Indicative (I)	big printing area
TSS-K2		1.8	250mm or customized	12*26mm hexagonal shape	galvanized low-carbon steel and ABS plastic covered	150	Pull-tight	Indicative (I)	big printing area
DH-K		1.8	220mm or customized	14*26mm hexagonal shape	galvanized low-carbon steel and ABS plastic covered	150	Fixed Length	Indicative (I)	
DH-K2		1.8	250mm or customized	14*27mm hexagonal shape	galvanized low-carbon steel and ABS plastic covered	150	Pull-tight	Indicative (I)	
TSS-CS3.5H02		3.5	300mm or customized	16.5*27.5mm Pentagon shape	galvanized low-carbon steel and ABS plastic covered	1000	Fixed Length	High Security (H)	high security seal ISO17712 compliant



# Shanghai Xinfan Industrial Corporation






## Cable Security Seals

DH-K4		2.5	250mm or customized	19*28*7mm	galvanized low-carbon steel and ABS plastic covered	150	Pull-tight	Indicative (I)	
TSS-K5		1.7	230mm or customized	11*24mm hexagonal shape	galvanized low-carbon steel and ABS plastic covered	150	Crank-locking type, unfixed length	Indicative (I)	big printing area, Crank-locking
TSS-K8		1.8	250mm or customized	32*33*8.5mm	zinc alloy die-casting and ABS plastic covered	100	Pull-tight	Indicative (I)	double-color plastic cover
NEW TSS-CF1.0T		1.0	200mm or customized	22*26*6mm	aluminum alloy	150	Pull-tight	Indicative (I)	
NEW TSS-CF1.5T		1.5	200mm or customized	19*25*6mm	aluminum alloy	250	Pull-tight	Security (S)	



# Shanghai Xinfan Industrial Corporation






## Cable Security Seals

NEW TSS-CF2.0T		2.0	200mm or customized	22*26*6mm	aluminum alloy	350	Pull-tight	Security (S)	
NEW TSS-CF2.5T		2.5	250mm or customized	20.5*25*6.3mm	aluminum alloy	500	Pull-tight	Security (S)	
NEW TSS-CF3.0T		3.0	250mm or customized	26*26*7.5mm	aluminum alloy	700	Pull-tight	Security (S)	
NEW TSS-CF3.5T		3.5	300mm or customized	25*27.6*8mm	aluminum alloy	1000	Pull-tight	High Security (H)	high security seal ISO17712 compliant
NEW TSS-CF4.0T		4.0	300mm or customized	25*25*7.4mm	aluminum alloy	1100	Pull-tight	High Security (H)	high security seal ISO17712 compliant



# Shanghai Xinfan Industrial Corporation





## Cable Security Seals

NEW TSS-CF5.0T		5.0	300mm or customized	28*37*9mm	aluminum alloy	1200	Pull-tight	High Security (H)	high security seal ISO17712 compliant
TSS-CF1.5-TINY		1.5	200mm or customized	14*24*5mm	aluminum alloy	150	Pull-tight	Indicative (I)	
TSS-PCF1.5		1.5	200mm or customized	22*28*8.5mm	zinc alloy die-casting and ABS plastic covered	150	Pull-tight	Indicative (I)	
TSS-TACS1.5T		1.5	200mm or customized	44*56.5*13.6mm	aluminum plus clear PE housing	150	Pull-tight	Indicative (I)	with a clear housing to protect the printings
TSS-TACS3.5T		3.5	300mm or customized	44*56.5*13.6mm	aluminum plus clear PE housing	1000	Pull-tight	High Security (H)	with a clear housing to protect the printings, ISO17712 compliant




# Shanghai Xinfan Industrial Corporation

## Cable Security Seals

TSS-TACS5. 0T		5.0	300mm or customized	44*56.5*13.6mm	aluminum plus clear PE housing	1200	Pull-tight	High Security (H)	with a clear housing to protect the printings, ISO17712 compliant
TSS-PCF2. 0-3LOCK		2.0	200mm or customized	30.5*33*5mm	galvanized low-carbon steel and ABS plastic covered	350	Pull-tight	Security (S)	triple locking system
TSS-CF2. 5T-STD		2.5	300mm or customized	26*50*8mm	aluminum alloy	500	Pull-tight	Security (S)	double locking system
TSS-CF2. 5-BTDL		2.5	300mm or customized	25*42*8mm	aluminum alloy	500	Pull-tight	Security (S)	double locking system



Cable Security Seals

TSS-CF2.5T BIGFLAG		2.5	250mm or customized	26*25*6.3mm	aluminum alloy	500	Pull-tight	Security (S)	
--------------------	---	-----	---------------------	-------------	----------------	-----	------------	--------------	--